## CTO1 Roller Conveyor Curve 24V








## Smart & flexible

The modular platform of Inther Conveyor Equipment (ICE) is unique due to the short installation and commissioning time. All components (both mechanical and electrical) come pre-installed in our modules, including cabling and the correct E-plan codes.

The smart and flexible modules are available in various widths and are suitable for transporting all common goods in intralogistics.





### Curve 24V

The CTO1 Roller Conveyor Curve 24V transports materials automatically using a programmed controller. Each zone is driven by a motor roller that drives the non-driven rollers by means of belting.

- > Fully modular. The bend can be up to 15 degrees each time it's expanded. This is the only modular conveyor bend in the world!
- Integrated and labeled cabling
- Fast installation time

#### **Technical specifications**

#### **General information**

Max. carrying weight 35 kg/zone
Transport speed Min. 0,05 / max. 2,2 m/sec.
Ambient temperature +5°C to +40°C

#### **Drive transport**

per engine

Voltage 24V DC
Drive 1 motor roller per zone
Drive coupling Round belts
Control Conveylinx AI
Power consumption 2A (Peak, ECO+ mode)

#### **Electrical connection**

Connection voltage 90-265V AC / 1-phase
Connectivity 0,9A (240V AC)
Connection plug 7/8" Female, 3 pins
Work switch Included
Sensor Retro-reflective,
installed and wired

#### **Dimensions**

 $\begin{array}{lll} LW \ effective \ width & 420/620 \ mm \\ \alpha \ Corner & 15^{\circ} \ / \ 30^{\circ} \ / \ 45^{\circ} \ / \ 60^{\circ} \ / \ 75^{\circ} \ / \ 90^{\circ} \\ TW \ module \ width & LW + 96 \ mm \\ P \ roller \ pitch \ inside \ bend & 72 \ mm \\ SF \ side \ guide & 80 \ mm \end{array}$ 

#### Side profile

SP Profile height 126 mm

#### Rollers

Material Steel 1.5 mm, galvanized,
with conical sleeve made
of polypropylene
Diameter 50 mm
Performance Round head







# Inther Conveyor Equipment

- The Netherlands (HQ)
  De Amfoor 15
  5807 GW Venray
  +31 478 50 25 75
- **USA** +1 866 292 8266
- China +86 512 65030958
- Germany+49 5224 98 58 78
- Belgium +32 3 336 07 35



info@inthergroup.com www.inthergroup.com

