





Smart & flexible

The modular platform of Inther Conveyor Equipment (ICE) is unique due to the short installation and commissioning time. All components (both mechanical and electrical) come pre-installed in our modules, including cabling and the correct E-plan codes.

The smart and flexible modules are available in various widths and are suitable for transporting all common goods in intralogistics.



Merge 24V

The CTO1 Roller Conveyor Merge 24V combines materials from two transport lines by sending the materials onto the track when there is an empty space in the material flow. The Merge 24V can also be used as an output path by using a KPO1 Pop-up Module to send materials left or right.

- > Fully modular
- > Integrated and labeled cabling
- > Fast installation time



Technical specifications

General information

Max. carrying weight Transport speed Ambient temperature


35 kg/zone Min. 0,05 / max. 2,2 m/sec. +5°C to +40°C

Drive transport

Voltage Drive Drive coupling Control Power consumption per engine 24V DC 1 motor roller per zone Round belts** Conveylinx AI 2A (Peak, ECO+ mode)

Electrical connection


Connection voltage Connectivity Connection plug Work switch Sensor 90-265V AC / 1-phase 0,9A (240V AC) 7/8" Female, 3 pins Included Retro-reflective, installed and wired



Dimensions

| Differisions | |
|--|---------------------------|
| LW effective width | 420/620 mm |
| ML max. module length | 1128 mm (width 420 mm) |
| | 1428 mm (width 620 mm) |
| TW module width | LW + 96 mm |
| P roller pitch | 75/100/125 mm |
| SF side guide | 80 mm |
| Side profile | |
| SP Profile height | 126 mm |
| Rollers | |
| Material | Steel 1,5 mm, galvanized* |
| Diameter | 50 mm |
| Performance | Round head** |
| | |
| | |
| * Optionally, the rollers can be provided with a | |

- Optionally, the rollers can be provided with a friction layer
- ** Optionally, the drive coupling and rollers can be equipped with a poly V-belt drive



Inther Conveyor Equipment

The Netherlands (HQ) De Amfoor 15 5807 GW Venray +31 478 50 25 75

- USA +1 866 292 8266
- China+86 512 65030958
- Germany +49 5224 98 58 78
- Belgium
 +32 3 336 07 35

info@inthergroup.com www.inthergroup.com



