



CT01 Roller Conveyor Straight Non Driven



Smart & flexible

The modular platform of Inther Conveyor Equipment (ICE) is unique due to the short installation and commissioning time. All components (both mechanical and electrical) come pre-installed in our modules, including cabling and the correct E-plan codes.

The smart and flexible modules are available in various widths and are suitable for transporting all common goods in intralogistics.



Straight Non Driven

The CT01 Roller Conveyor Straight Non Driven is a gravity conveyor where materials are transported by hand or by means of gravity down a slope. This conveyor is often used for areas where materials are collected or set up manually.

Technical specifications

General information

Max. carrying weight	35 kg
Ambient temperature	+5°C to +40°C

Dimensions

LW effective width	420/620 mm
ML max. module length	3000 mm
TW module width	LW + 96 mm
P roller pitch	75/100/125 mm
SF side guide	80 mm


Side profile

SP Profile height	126 mm
-------------------	--------

Rollers

Material	Steel 1,5 mm, galvanized*
Diameter	50 mm

* Optionally, plastic rollers can be used, these have a lower rolling resistance (for less heavy products)



Inther

Conveyor Equipment

 **The Netherlands (HQ)**
De Amfoor 15
5807 GW Venray
+31 478 50 25 75

 **USA**
+1 866 292 8266

 **China**
+86 512 65030958

 **Germany**
+49 5224 98 58 78

 **Belgium**
+32 3 336 07 35

info@inthergroup.com
www.inthergroup.com



INTHER
improving intralogistics